



GHKE-52S-DF-TL

Fork Properties

900 Kgs. Load Capacity Forged Kingpinless Castors

- Single piece forged alloy steel top plate & fork base
- Precision CNC machined raceways
- Induction hardened raceways ensure swivel head longevity
- Totally sealed swivel head with grease nipple
- 6mm thick fabricated construction of forks robotically welded inside & outside to 65mm fork spacing
- 12mm Wheel Axle
- Finish: Zinc plate; ROHS compliant or Black polymer color coated
- Options : 4 way directional lock, Total lock, Wheel face break

Wheel Properties

Muvtons Drop Forged Wheels are hot forged from Alloy Steels and can be used in the roughest of applications on the poorest of floors. these are virtually in-destructible within their capacity range .tread faces are fully machined for easy maneuverability - these wheels offer high abrasion and oil resistance . Wheel Bearing Options: Sealed precision ball bearings, tapered roller bearings or roller bearings. Temperature range:-100° C to +600° C.

Technical Data

Castor Type	Swivel Castor with Brake
Wheel Material	Alloy Steel
Wheel Dia(mm)	125
Tread Width(mm)	50
Load Capacity(kg)	900
Wheel Bearing	Ball Bearing
Overall Height(mm)	165
Swivel Radius(mm)	95
Swivel Radius TL(mm)	110
Top Plate(mm)	138 x 110
Bolt Hole Dia(mm)	105 x 75-80
Non Marking	-
Heat Resistant	yes
Noise Reduction	-

