












GRDE Castors with SAS Series Polyurethane Wheels

Muvtons Premium Polyurethane treaded wheels $93^{\circ} \pm 3^{\circ}$ Shore A, firmly bonded to precision machined cast iron cores offer low rolling resistance, smooth & noiseless running, are non-marking and floor protective. These wheels possess high abrasion & cut resistance and are resistant to tearing. Tested & Guaranteed against bond failures. Wheel Bearing Options : Sealed precision ball bearings, tapered roller bearings or roller bearings. Colour: Light Brown. Temperature range : -20°C to $+85^{\circ} \text{C}$. Tread Options : Anti-static ; conductive wheels are available.



Part No. Swivel Castor	Part No. Swivel with Total Lock	Part No. Rigid Castor (mm)	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Swivel Radius with TL (mm)	Top Plate (mm)	Bolt Hole Centers (mm)	Attaching Bolt Size (mm)	Load Cap. (kgs).
										
GRDE-8575S-SAS	GRDE-8575S-SAS-TL	GRDE-8575R-SAS	85 x 75	144	85	80	150 x 110	105 x 80 Slotted to 121/59	12	650
GRDE-42S-SAS	GRDE-42S-SAS-TL	GRDE-42R-SAS	100 x 50	150	95	98				400
GRDE-52S-SAS	GRDE-52S-SAS-TL	GRDE-52R-SAS	125 x 50	177	115	115				550
GRDE-62S-SAS	GRDE-62S-SAS-TL	GRDE-62R-SAS	150 x 50	200	130	135				750
GRDE-82S-SAS	GRDE-82S-SAS-TL	GRDE-82R-SAS	200 x 50	250	163	162				1000
GRDE-102S-SAS	GRDE-102S-SAS-TL	GRDE-102R-SAS	250 x 50	300	197	195				1200
GRDE-122S-SAS	GRDE-122S-SAS-TL	GRDE-122R-SAS	300 x 50	350	232	232				1400