












SAB Forged Precision Bearing Castors with SEB Series Elastic Rubber Tyred Wheels

Muvtons - black Elastic Rubber tyred wheels firmly chemically bonded to precision machined cast iron cores. Highly resilient 75° ±5° Shore A rubber provides very smooth and silent running. Can be used for power towing applications by suitably de-rating the load capacity. Wheel Bearing Options : Sealed precision ball bearings, tapered roller bearings or roller bearings. Temperature range : -20° C to +75° C. Tread Options : Anti-static; conductive and oil resistant wheels are available.



Part No. Swivel Castor	Part No. Swivel with Total Lock	Part No. Rigid Castor (mm)	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Swivel Radius with TL (mm)	Top Plate (mm)	Bolt Hole Centers (mm)	Attaching Bolt Size (mm)	Load Cap. (kgs).
										
SAB-42S-SEB	SAB-42S-SEB-TL	SAB-42R-SEB	100 x 50	150	95	95	138 x 110	105 x 75-80	10	210
SAB-52S-SEB	SAB-52S-SEB-TL	SAB-52R-SEB	125 x 50	175	120	110				275
SAB-62S-SEB	SAB-62S-SEB-TL	SAB-62R-SEB	150 x 50	200	130	135				350
SAB-82S-SEB	SAB-82S-SEB-TL	SAB-82R-SEB	200 x 50	250	155	160				450
SAB-102S-SEB	SAB-102S-SEB-TL	SAB-102R-SEB	250 x 50	300	198	195				500