












GRDE Castors with DF Series Drop Forged Steel Wheels

Muvtons Drop Forged Wheels are hot forged from Alloy Steels and can be used in the roughest of applications on the poorest of floors. These are virtually in-destructible within their capacity range. Tread faces are fully machined for easy maneuverability - these wheels offer high abrasion and oil resistance. Wheel Bearing Options : Sealed precision ball bearings, tapered roller bearings or roller bearings. Temperature range : -100° C to +600° C.



Part No. Swivel Castor	Part No. Swivel with Total Lock	Part No. Rigid Castor (mm)	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Swivel Radius with TL (mm)	Top Plate (mm)	Bolt Hole Centers (mm)	Attaching Bolt Size (mm)	Load Cap. (kgs).
										
GRDE-42S-DF	GRDE-42S-DF-TL	GRDE-42R-DF	100 x 50	150	95	98	150 x 110	105 x 80 Slotted to 121/59	12	800
GRDE-52S-DF	GRDE-52S-DF-TL	GRDE-52R-DF	125 x 50	177	115	115				1000
GRDE-62S-DF	GRDE-62S-DF-TL	GRDE-62R-DF	150 x 50	200	130	135				1200
GRDE-82S-DF	GRDE-82S-DF-TL	GRDE-82R-DF	200 x 50	250	163	162				1500