












# DABE50 Forged Twin Wheel Castors with SFS Series Solid Elastomer Wheels

Muvtons exclusively designed "Real Solid" Elastomer Wheels - produced from premium liquid cast polyurethane 73° ±3° Shore D mechanically & chemically locked to a non-corrosive metallic core that holds the wheel bearings and also provides structural rigidity under heavy loads. These wheels resist compression set, have excellent resilience for easy movement even under high loads and expel floor debris. Can be used for corrosive applications with suitable bearings. They are non-marking and floor protective. Tested & Guaranteed against bond failures.

Wheel Bearing Options : Sealed precision ball bearings, tapered roller bearings or roller bearings. Temperature range : -20° C to +85° C. Tread Options : Anti-static ; conductive wheels are available.



Part No. Swivel Castor	Part No. Swivel with Wheel Brake	Part No. Rigid Castor (mm)	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Swivel Radius with WFB (mm)	Top Plate (mm)	Bolt Hole Centers (mm)	Attaching Bolt Size (mm)	Load Cap. (kgs).
										
DABE50-63S-SFS	DABE50-63S-SFS-WFB	DABE50-63R-SFS	150 x 75 x 2	212	160	310	200 x 160	160 x 120	16	2200
DABE50-83S-SFS	DABE50-83S-SFS-WFB	DABE50-83R-SFS	200 x 75 x 2	264	190	350				2300
DABE50-103S-SFS	DABE50-103S-SFS-WFB	DABE50-103R-SFS	250 x 75 x 2	314	220	375				2700
DABE50-123S-SFS	DABE50-123S-SFS-WFB	DABE50-123R-SFS	300 x 75 x 2	375	245	395				3100