







GHKE Castors with SEB Series Elastic Rubber Type Wheels

Muvtons - black Elastic Rubber tyred wheels firmly chemically bonded to precision machined cast iron cores. Highly resilient 75° ±5° Shore A rubber provides very smooth and silent running. Can be used for power towing applications by suitably de-rating the load capacity. Wheel Bearing Options : Sealed precision ball bearings, tapered roller bearings or roller bearings. Temperature range : -20° C to +75° C. Tread Options : Anti-static; conductive and oil resistant wheels are available.



| Part No. Swivel Castor | Part No. Swivel with Total Lock | Part No. Rigid Castor (mm) | Wheel Dia x Tread Width (mm) | Overall Height (mm) | Swivel Radius (mm) | Swivel Radius with TL (mm) | Top Plate (mm) | Bolt Hole Centers (mm) | Attaching Bolt Size (mm) | Load Cap. (kgs). |
|--|--|--|--|--|--|--|--|--|--|--|
|  |  |  |  |  |  |  |  |  |  |  |
| GHKE-42S-SEB | GHKE-42S-SEB-TL | GGSE-42R-SEB | 100 x 50 | 140 | 77 | 90 | 138 x 110 | 105 x 75-80 | 10 | 210 |
| GHKE-52S-SEB | GHKE-52S-SEB-TL | GGSE-52R-SEB | 125 x 50 | 165 | 95 | 110 | | | | 275 |
| GHKE-62S-SEB | GHKE-62S-SEB-TL | GGSE-62R-SEB | 150 x 50 | 195 | 115 | 140 | | | | 350 |
| GHKE-82S-SEB | GHKE-82S-SEB-TL | GGSE-82R-SEB | 200 x 50 | 245 | 152 | 163 | | | | 450 |
| GHKE-102S-SEB | GHKE-102S-SEB-TL | GGSE-102R-SEB | 250 x 50 | 295 | 190 | 197 | | | | 500 |