












DABLP Forged Twin Wheel Castors with SFS Series Solid Elastomer Wheels

Muvtons exclusively designed "Real Solid" Elastomer Wheels - produced from premium liquid cast polyurethane 73° ±3° Shore D mechanically & chemically locked to a non-corrosive metallic core that holds the wheel bearings and also provides structural rigidity under heavy loads. These wheels resist compression set, have excellent resilience for easy movement even under high loads and expel floor debris. Can be used for corrosive applications with suitable bearings. They are non-marking and floor protective. Tested & Guaranteed against bond failures. Wheel Bearing Options : Sealed precision ball bearings, tapered roller bearings or roller bearings. Temperature range : -20° C to +85° C. Tread Options : Anti-static ; conductive wheels are available.



Part No. Swivel Castor	Part No. Swivel with Wheel Brake	Part No. Rigid Castor (mm)	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Swivel Radius with WFB (mm)	Top Plate (mm)	Bolt Hole Centers (mm)	Attaching Bolt Size (mm)	Load Cap. (kgs).
										
DABLP-522S-SFS	DABLP-522S-SFS-WFB	DABLP-522R-SFS	125 x 50 x 2	185	120	245	175 x 140	140 x 105	12	1000
DABLP-622S-SFS	DABLP-622S-SFS-WFB	DABLP-622R-SFS	150 x 50 x 2	212	140	265				1350
DABLP-822S-SFS	DABLP-822S-SFS-WFB	DABLP-822R-SFS	200 x 50 x 2	264	175	303				1600
DABLP-1022S-SFS	DABLP-1022S-SFS-WFB	DABLP-1022R-SFS	250 x 50 x 2	314	212	340				2000
DABLP-1222S-SFS	DABLP-1222S-SFS-WFB	DABLP-1222R-SFS	300 x 50 x 2	365	240	368				2000