












GGSE Castors with SZS Series Soft Polyurethane Wheels

Muvtons Premium Soft Durometer Polyurethane treaded wheels $83^{\circ} \pm 3^{\circ}$ Shore A, firmly bonded to precision machined cast iron cores. These wheels have been designed in response to noise problems and allow loads to be cushioned. The use of 'lively' polyurethane materials allows these wheels to 'flex & roll' over debris and obstacles without picking up objects. They are non-marking and floor protective. Tested & Guaranteed against bond failures. Wheel Bearing Options : Sealed precision ball bearings, tapered roller bearings or roller bearings. Temperature range : -20°C to $+85^{\circ}\text{C}$. Tread Options : Anti-static ; conductive wheels are available.



Part No. Swivel Castor	Part No. Swivel with Total Lock	Part No. Rigid Castor (mm)	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Swivel Radius with TL (mm)	Top Plate (mm)	Bolt Hole Centers (mm)	Attaching Bolt Size (mm)	Load Cap. (kgs).
										
GGSE-42S-SZS	GGSE-42S-SZS-TL	GGSE-42R-SZS	100 x 50	143	85	105	138 x 110	105 x 75-80	10	250
GGSE-52S-SZS	GGSE-52S-SZS-TL	GGSE-52R-SZS	125 x 50	165	101	110				350
GGSE-62S-SZS	GGSE-62S-SZS-TL	GGSE-62R-SZS	150 x 50	190	120	140				450
GGSE-82S-SZS	GGSE-82S-SZS-TL	GGSE-82R-SZS	200 x 50	241	156	163				600