

HSE-45 Hot Stamping Machine

Advantages

- For a wide variety of hot stamping applications and for stamping on to different substrates.
- Dwell time and cooling time are adjustable to achieve special stamping effects such as multi-level embossing and refractive engraving.
- Open end design allows big paper format larger than work table size.
- Settings can be easily keyed in with the HMI.
- Die setting is relatively easy.
- Programmable long and short foil feeds to minimize foil wastage.
- Electrical components are of reliable European and Japanese brands.
- Optional reel to reel system is available.

Specifications

Output kg	45,000
Size of Heating Plate mm	500 X 530
Stroke mm	50
Size of Work Table mm	580 X 760
Maximum Paper Size mm	635 X 890
Max Solid Stamping Area mm	200 X 220
Maximum Daylight mm	70
Throat Depth mm	330
Maximum Foil Pull mm	530
Foil Feed Device (motor)	One set
Foil Feed Direction	Side
Heater Capacity kW	3.6
Temperature Control degree Celsius	Max 200 °C
Dwell Time second	0-9.9
Motor Output kW	4
Power Source	3 ph/380v/50Hz- 8.5 kW
Machine Dimensions (W x D x H) m	1.85 X 1.23 X 1.6
Net Weight kg	900



Hong Kong Office
Tel: +852 2896 6829
Fax: +852 2558 0855
Website: www.lckhk.com

Shenzhen Office
Tel: +86 755 2739 6676
Fax: +86 755 2739 5576