






# GRDE Castors with MCNY Series Cast Polyamide Wheels

Muvtons MCNY Wheels produced from high impact resistant cast polyamide are the ultimate choice for extremely high loads where metallic wheels are not an option. These wheels possess very high abrasion resistance and offer low rolling resistance under extreme loads. Can be used in corrosive applications. Wheel Bearing Options : Sealed precision ball bearings, tapered roller bearings or plain bore. Temperature range : -30° C to +80° C.



Part No. Swivel Castor	Part No. Swivel with Total Lock	Part No. Rigid Castor (mm)	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Swivel Radius with TL (mm)	Top Plate (mm)	Bolt Hole Centers (mm)	Attaching Bolt Size (mm)	Load Cap. (kgs).
										
GRDE-42S-MCNY	GRDE-42S-MCNY-TL	GRDE-42R-MCNY	100 x 50	150	95	98	150 x 110	105 x 80 Slotted to 121/59	12	1400
GRDE-52S-MCNY	GRDE-52S-MCNY-TL	GRDE-52R-MCNY	125 x 50	177	115	115				1500
GRDE-62S-MCNY	GRDE-62S-MCNY-TL	GRDE-62R-MCNY	150 x 50	200	130	135				1500
GRDE-82S-MCNY	GRDE-82S-MCNY-TL	GRDE-82R-MCNY	200 x 50	250	163	162				1500
GRDE-102S-MCNY	GRDE-102S-MCNY-TL	GRDE-102R-MCNY	250 x 50	300	197	195				1500