

<b>Ethernet</b>	
Standards	IEEE802.3, IEEE802.3u, IEEE802.3x
Processing type	Store and Forward
Flow control	IEEE802.3X flow control, backpressure flow control
<b>Interface</b>	
RJ-45 Ports	10/100 BASET(X) auto negotiation speed Full/Half-duplex mode, and auto MDI/MDI-X connection
LED Indicators	Power, 10/100M
<b>Power</b>	
Connector	5.08mm 5-pin Terminal Block
Input Voltage	9-48 VDC
Input Current	0.35A
Power Consumption	3.15W max.
Reverse Polarity Protection	Present
<b>Approval</b>	
EMC	FCC Class A, CE Class A
EMS	ESD Level 2, RS Level 2, EFT Level 2, Surge Level 2, CS Level 2, PFMF Level1, DIP.
Safety	UL60950-1 2nd ED./CSA C22.2 NO.60950-1-07 2nd ED.
Shock	IEC 60068-2-27
Drop	ISTA Test procedure 2A
Vibration	IEC 60068-2-64
MTBF	58.86 years
RoHS	Lead(Pb) Free
<b>Environment</b>	
Operating	-10°C~70°C (14°~158°F)
Storage	-40°~85°C (-40°~185°F)
Ambient Relative Humidity	5~95%RH(Non-condensing)
<b>Mechanical</b>	
(W x H x D)	45.3mm x110mm x 89.6mm
Material	Aluminum
Weight	460g
<b>Warranty</b>	5 years